



- NEW CRAWLSPACE (UNHEATED)
 - RSI MIN-INSULATION
 - SPRAY FOAM INTO NEW FL. DIST. ABOVE
 - 6MIL POLY W/ B W/ CRUSHED 4" STONE COVERED ON TOP

(3) LOCATIONS WHERE EX. FTG WALLS AND NEW FTG WALLS MET PROVIDE DOWELS ALL WAY DOWN TO EX. FTG. NEW FTG'S USE 1-10M REBAR 1/2" DIA. TOP TO BOTTOM OF FTG WALL (VERIFY ON SITE)

- NEW STAIRCASE IS MADE OF WOOD
 - UNDER STAIRCASE NEW FOURIN CONG. FLOOR, 4" THK.
 - 1" CONG. SLAB (ZOMPA)
 - 6" CRUSHED STONE COMPACTED LEVEL W/ EX. CONG. FL. IN EX. BASEMENT.

- EX. BASEMENT FLOOR PLAN -
 - SCALE: 1/4" = 1'-0"
 - NEW CRAWLSPACE ADDITION REAR YARD -

SHEET TITLE - BASEMENT FLOOR PLAN -
 - EXISTING BASEMENT FL.
 - NEW CRAWLSPACE FL ADDITION

LOCATION: 6013 ATLAS STREET
 NIAGARA FALLS, ONT.

CLIENT: MR. T. McMONEY
 DATE: JULY 17, 2023
 CH. BY: S. DEROSE
 DR. BY: L. MOONE
 SCALE: 1/4" = 1'-0"
 SH. N