



- WRAPPING – APPROVED TREE WRAP FROM TOP OF BALL TO 300mm ABOVE FIRST BRANCH. SECURE WITH BINDER TWINE, WOUND OPPOSITE TO WRAPPING. SECURED TOP, MIDDLE AND BOTTOM.
- GUYING – TWO 40x40x5mm STEEL "T" BARS, MINIMUM 2400mm LONG, PREDRILLED TO RECEIVE #10 WIRE THREADED THROUGH 15mm RUBBER HOSE TO SUPPORT TREE. PAINT "T-BAR" CITY OF NIAGARA FALLS STANDARD HIGH GLOSS GREEN ENAMEL.
- 100mm SHREDDED WOODCHIP MULCH OVER FIBRE MATTING AS PER SPECIFICATIONS.
- 150mm DIA. BLACK DRAIN PIPE ANIMAL GUARD WHERE REQUIRED
- MAINTAIN ORIGINAL GRADE OF TREE BASE AFTER PLANTING OR SLIGHTLY HIGHER TO SUIT SITE SOIL CONDITIONS.
- 100mm DEEP, 600mm DIA. SAUCER
- PLANTING SOIL TO BE IMPORTED TRIPLE MIX AND EXISTING MATERIAL EXCEPT WHEN PLANTING IN SHRUB BEDS. SOIL SHALL BE FREE OF LUMPS, STONES ROCKS AND ANY OTHER INORGANIC MATERIAL.
- CUT AND REMOVE BURLAP FROM TOP 1/3 OF ROOT BALL.

NOTES:

1. PRUNING – TO SUIT SPECIES – PRUNE BRANCHES BY 1/3 TO REMOVE DAMAGED OR OBJECTIONABLE BRANCHES FOLLOWING PROPER HORTICULTUREL PRACTICE. DO NOT PRUNE LEADERS.
2. SOIL MIXTURE SHOULD BE FIRMLY COMPACTED TO ELIMINATE AIR POCKETS AND TO PREVENT SETTLEMENT.
3. THIS DETAIL DOES NOT REPRESENT ANY PARTICULAR SPECIES.

(< 60mm DIA) DECIDUOUS TREE PLANTING DETAIL



4310 QUEEN STREET
 NIAGARA FALLS, ONTARIO
 L2E 6X5

COMMUNITY SERVICES DEPARTMENT
 PARKS, RECREATION & CULTURE
 TELEPHONE : (905) 356-7521 FAX : (905) 356-7404

scale	N.T.S
date	JULY 1993
date revised	JANUARY 13, 2006
drawing no.	D2-950-01
park no.	