



THE CORPORATION OF THE CITY OF NIAGARA FALLS

RFT6-2020

**SUPPLY & DELIVERY OF
SINGLE AXLE DUMP TRUCKS**

SPECIFICATIONS

**TWO (2) NEW LATEST MODEL
11,000 LB G.V.W. SINGLE AXLE TRUCKS WITH DUAL WHEELS,
CREW CAB AND CONTRACTORS DUMP BOX & HOIST**

NAME OF COMPANY (DEALER): _____

ITEM/CATEGORY	CITY REQUIREMENTS	BIDDER TO STATE SPECIFICATIONS
Make		
Year		
Model	350 series or equivalent	
G.V.W	11,000 lbs. minimum, with DRW – if otherwise state	
Cab	Standard 5 passenger, 4-door crew cab	
Box	See Specs	
Engine	Gasoline V8 engine with approximately 350 ft./lb. torque at 4200 rpm Must include pollution emission control as required by law	
Fuel Efficiency		
Transmission	Heavy-duty 6 speed automatic overdrive transmission with cooler or equivalent.	
Cab to Axle	60" C.A.	
Wheel Base	State	
Suspension	Front capacity of 2,300 lbs. each and rear spring capacity of 4,600 lbs. each at ground Rear auxiliary springs 500 lbs. minimum each STATE:	
Axles	5,000 lbs. minimum front capacity and 10,000 lbs. minimum at rear Heavy duty shock absorbers front. STATE:	

**THE CORPORATION OF THE CITY OF NIAGARA FALLS
REQUEST FOR QUOTATION – SUPPLY - RFT6-2020
SUPPLY & DELIVERY OF SINGLE AXLE DUMP TRUCKS**

SPECIFICATIONS – Two (2) New Latest Model 11,000 Lb. G.V.W. Single Axle Trucks with Dual Wheels, Crew Cab and Contractors Dump Box & Hoist cont'd.

NAME OF COMPANY (DEALER): _____

ITEM/CATEGORY	CITY REQUIREMENTS	BIDDER TO STATE SPECIFICATIONS
Steering	Power steering required.	
Air Cleaner	Shall be heavy duty dry type.	
Tires	Shall be steel belted tubeless type size 265R18. Front highway tread and rear tires being snow and mud tread dual rear wheels - if otherwise state.	
Splash Guards	One pair installed in front of and behind rear wheels.	
Brakes	Dual type hydraulic heavy duty ABS with parking brake.	
Electrical System	Shall be 12 volt system and have a heavy duty 70 amp hour battery with a 150 amp alternator suitable for two-way radio - if otherwise state. 110V AC engine block heater. Suppression type wiring to eliminate ignition noise in two-way radio. Factory trailer package wiring harness. Must have electric brake controller in cab wired to 7 prong commercial plug at rear.	
Windshield Wipers	Shall be dual electric two speed, variable delay speeds.	
Windshield Washers	Dual windshield washers of type recommended by manufacturer.	
Heater & Defroster	Heavy duty standard hot water type recommended by manufacturer.	
Seats	Heavy duty vinyl seats or equivalent Full width bench seat must be fully adjustable.	
Lights	Shall be equipped with electric headlights, dome lights, combination stop, tail and backup lights, directional signals of four-way flasher type, together with all other lights as required by law for vehicles of this type.	

**THE CORPORATION OF THE CITY OF NIAGARA FALLS
REQUEST FOR QUOTATION – SUPPLY - RFT6-2020
SUPPLY & DELIVERY OF SINGLE AXLE DUMP TRUCKS**

SPECIFICATIONS – Two (2) New Latest Model 11,000 Lb. G.V.W. Single Axle Trucks with Dual Wheels, Crew Cab and Contractors Dump Box & Hoist cont'd.

NAME OF COMPANY (DEALER): _____

ITEM/CATEGORY	CITY REQUIREMENTS	BIDDER TO STATE SPECIFICATIONS
	<p>Shall be equipped with backup alarm.</p> <p>Taillights and clearance must be LED type.</p> <p>The supplier is not to cut or tap into any of the existing chassis wiring.</p> <p>All lighting and reflectors must meet current CMVSS.</p>	
Equipment	<p>Trailer hitch HD with Pintle type front bumper.</p> <p>Two outside rear-view mirrors, 7" X 16", type and must have full visibility to back sides of box.</p> <p>Water temperature indicator, turning signals, oil pressure indicator and alternator indicator.</p> <p>Power windows and locks.</p> <p>Anti-freeze to -40 degrees Fahrenheit.</p> <p>All standard equipment to be supplied as per manufacturer's features including AM/FM radio.</p> <p>Factory installed air conditioning with environment friendly refrigerant.</p>	
Dican Camera System	<p>Di-SVC1080LCS.</p> <p>Supply Full HD 3M pixel CMOS Image sensor, tamper resistant.</p> <p>housing, wide angle lens 170degree; 1080P Full HD 1920X1080 with 30 fps recording; internal battery; internal GPS and 3 axis accelerometer;</p> <p>Audio recording (optional); Internal microphone; 32GB Micro-SD.</p> <p>Commercial Grade Two Year Warranty</p>	

**THE CORPORATION OF THE CITY OF NIAGARA FALLS
REQUEST FOR QUOTATION – SUPPLY - RFT6-2020
SUPPLY & DELIVERY OF SINGLE AXLE DUMP TRUCKS**

SPECIFICATIONS – Two (2) New Latest Model 11,000 Lb. G.V.W. Single Axle Trucks with Dual Wheels, Crew Cab and Contractors Dump Box & Hoist cont'd.

NAME OF COMPANY (DEALER): _____

ITEM/CATEGORY	CITY REQUIREMENTS	BIDDER TO STATE SPECIFICATIONS
	<p>Installation Included. NO Alternative.</p>	
<p>Dump Body</p>	<p>Contractors dump body.</p> <p>Premium grade, 5083-H321 bright finish all aluminum dump body manufactured by Eloquip Ltd. Model #AA60149 and suitable for 60" cab to axle, or equivalent manufacturer.</p> <p>Inside length shall be 8' Outside width shall be 96"</p> <p>Sides shall be 18" fold down with stainless locking handles, 3/16" thick inside skin and 1/8" thick formed outside skin.</p> <p>Side hinges shall be made of 5/8" thick plate, complete with full width tie down tube - stops to be installed when sides are dropped down.</p> <p>Tailgate to be double acting with chains, 24" high, 3/16" thick inside skin and 1/8" thick formed outside skin with 3" wide side members - to be manually operated with front controls; may be custom for debris attachment.</p> <p>Rear corner posts to be formed with 3/16" outside and 1/4" inside material thickness.</p> <p>Sideboard gussets for 2 X 6 hardwood side boards.</p> <p>Floor to be 1/4" aluminum plate with 2/5" channels on 12" centers.</p> <p>Side rail to be 4" X 1/4" formed.</p> <p>Front wall to be 3/16" thickness Main frame to be aluminum 1/4" X 6"</p>	

**THE CORPORATION OF THE CITY OF NIAGARA FALLS
REQUEST FOR QUOTATION – SUPPLY - RFT6-2020
SUPPLY & DELIVERY OF SINGLE AXLE DUMP TRUCKS**

SPECIFICATIONS – Two (2) New Latest Model 11,000 Lb. G.V.W. Single Axle Trucks with Dual Wheels, Crew Cab and Contractors Dump Box & Hoist cont'd.

NAME OF COMPANY (DEALER): _____

ITEM/CATEGORY	CITY REQUIREMENTS	BIDDER TO STATE SPECIFICATIONS
	<p>channel Box to have six (6) flush mounted tie down rings located in dump body floor.</p> <p>Roll up mesh tarp with hand crank mounted at a suitable height to be operated from the ground will be installed - guards required on any pull, belts, chains, etc.</p> <p>Shall have heavy-duty under body electric/hydraulic hoist with cab mounted controls - power up and down. PTO with Hydraulic Pump off of Transmission is acceptable.</p> <p>Supply and install one stationary cabinet between truck cab and dump box, pre-build meeting. Cabinet to be aluminum construction using 3/16" 5083 grade aluminum. Cabinet top to be level with roof of cab and bottom to be level with lower edge of cab and same width of cab. Cabinet to be approximately 16" wide. Cabinet will come with cam lock mechanism, keeping door closed tightly top and bottom, with key locking mechanism. Minimum two through shelves</p> <p>Aluminum splash guards in front of wheels (ALL FASTENERS TO BE STAINLESS STEEL).</p> <p>Mud flaps at rear of wheels.</p> <p>Aluminum cab steps required on both sides - 300lb capacity.</p> <p>Stainless steel or aluminum hinges and hardware required where possible.</p> <p>Two LED Star 16031 beacon lights mounted on right and left sides. Star LED series mini bar. One stationary on right side top of</p>	

**THE CORPORATION OF THE CITY OF NIAGARA FALLS
REQUEST FOR QUOTATION – SUPPLY - RFT6-2020
SUPPLY & DELIVERY OF SINGLE AXLE DUMP TRUCKS**

SPECIFICATIONS – Two (2) New Latest Model 11,000 Lb. G.V.W. Single Axle Trucks with Dual Wheels, Crew Cab and Contractors Dump Box & Hoist cont'd.

NAME OF COMPANY (DEALER): _____

ITEM/CATEGORY	CITY REQUIREMENTS	BIDDER TO STATE SPECIFICATIONS
	cabinets and left side beacon to rise with box. Fuel filler mounted to provide easy access without raising dump body.	
Dump Box Hydraulics	Pump assembly not to be mounted inside cab Pump capacity and operating PSI in GPM's. Hydraulic pump to have a protective cover, reservoir filter, magnetic drain plug & sight gauge. MUST HAVE PROTECTIVE COVER OVER PUMP. SAE 100 R1 minimum rated hydraulic hosing required. Hosing routed and secured for no rubbing. Transmission mounted Pump is acceptable.	
Dump Box Warranty	Warranty period to be 1 year minimum, for parts, labor, service, delivery, and charges.	
Mfg.'s Warranty	Minimum 5 year corrosion warranty. Minimum 3 year bumper-to-bumper. State powertrain warranty.	
Paint	Cab to be painted manufacturer's white.	
Service	Service and parts must be available within a fifty (50) mile radius of the City of Niagara Falls.	
Manuals	Operators and service manuals and line ticket must be supplied with vehicle. Manuals on CD acceptable. Diagnostic software.	
Delivery	Meeting to be scheduled with dump box manufacturer before proceeding with building of dump box. Delivery to be made to the Municipal Service Centre, 3200 Stanley Avenue, Niagara Falls, Ontario.	

**THE CORPORATION OF THE CITY OF NIAGARA FALLS
REQUEST FOR QUOTATION – SUPPLY - RFT6-2020
SUPPLY & DELIVERY OF SINGLE AXLE DUMP TRUCKS**

SPECIFICATIONS – Two (2) New Latest Model 11,000 Lb. G.V.W. Single Axle Trucks with Dual Wheels, Crew Cab and Contractors Dump Box & Hoist cont'd.

NAME OF COMPANY (DEALER): _____

ITEM/CATEGORY	CITY REQUIREMENTS	BIDDER TO STATE SPECIFICATIONS
	Weight slip to be supplied upon delivery of vehicle time from date of order.	
License	To be supplied by municipality	