



THE CORPORATION OF THE CITY OF NIAGARA FALLS

ADDENDUM #1

**RFT1-2022
SUPPLY & DELIVERY OF FOUR (4) SNOW PLOW TRUCKS**

CLOSING DATE: Thursday, February 3rd, 2022 at 2:00 p.m. local time

This addendum shall form an integral part of the Request for Tender (RFT) documents for the above noted RFT and shall be read in conjunction therewith. This addendum shall, however, take precedence over all requirements as it pertains to the particular and specific items noted below.

This addendum must be signed by the Bidder in the appropriate space and must be attached to the Bidder's Tender submission at the stated time of the closing of the RFT or prior to this time. Tender submissions not including this addendum may be rejected.

CLARIFICATIONS

SPECIFICATIONS & CONFIRMATION:

SNOW & ICE CONTROL EQUIPMENT - SPEC. #31-2-B, SECTION #17 HOIST - Mailhot Nitride 3 stage telescopic hoist, "C" series, changed from Model CS-130-5-3 to Model CS-94-5-3.

- **SPEC. #31D-2-B:**
Remove: Page 7 of 31 of the original RFT document.
Replace with: Page 7 replacement - page 2 of this Addendum #1.

The Bidder shall take due notice of the above noted changes and make allowance for same in the Tender to be submitted to the City of Niagara Falls.

COMPANY NAME:	
TENDERER'S SIGNATURE:	
TENDERER'S NAME: (Please Print)	
DATE:	

**THE CORPORATION OF THE CITY OF NIAGARA FALLS
REQUEST FOR TENDER-SUPPLY
RFT1-2022
SUPPLY & DELIVERY OF FOUR (4) SNOW PLOW TRUCKS**

**SPEC. #31D-2-B
Page 7 of 31**

SPECIFICATIONS & CONFIRMATION - SNOW AND ICE CONTROL EQUIPMENT

16. **HYDRAULIC CYLINDERS (Cont'd)** **SPECIFY**
- Part number and date code to be stamped into the outside of the barrel _____ YES/NO
17. **HOIST** **SPECIFY**
- Mailhot Nitride 3 stage telescopic hoist, "C" series **Model CS-94-5-3** _____ YES/NO
- MAKE:** _____
- MODEL:** _____
- Top lift design with no hoist doghouse protruding inside the spreader body _____ YES/NO
- Hoist capacity shall be 20 ton @ 2,000 P.S.I. _____ YES/NO
- Hoist cylinder shall be rod sealed _____ YES/NO
- Cylinder stroke shall be 94 inches _____ YES/NO
- Dump box dump angle shall be variable to 50 degrees from horizontal _____ YES/NO
- Rear dump hinge diameter shall be 2 1/2" inches _____ YES/NO
- The body to be equipped with two twin positive locking support brace's, one right side and one left side incorporated into the rear body dump hinges _____ YES/NO
18. **TAILGATE** **SPECIFY**
- Tailgate shall be double acting and open to 90 degrees from hinge pins, and will lie down to provide longer floor area _____ YES/NO
- Tailgate sheet shall be 1/4" 5083-H321 aluminum _____ YES/NO
- Tailgate sheet to be reinforced with formed horizontal stiffeners fabricated from 1/4" 5083-H321 aluminum _____ YES/NO

COMPANY NAME: _____ **SIGNATURE:** _____